

Introducing the Nabors SmartRig® Fleet

Engineered For Excellence, The Nabors Rig Fleet Delivers Unmatched Performance

Performance excellence is delivered across safety, efficiency and sustainability to drive success in today's competitive industry landscape.

This fleet represents one of the world's youngest and most advanced fleets in land drilling industry, capable of tackling the toughest operational challenges.

Conquer the Unconventional

Purpose-built for factory drilling, the PACE® class drilling rigs are designed to optimize multi-well development programs and reduce flat time

- Walking systems enabling best-in-class well-towell move times
- Modular platform to streamline rig move times over short distances
- Highest horsepower, pressure and torque in its class to maximize lateral lengths

Unleash Automation and Performance

Equipped with the SmartROS® rig operating system, Nabors SmartRig® fleet allows you to deploy our full suite of technologies for automated processes that:

- Streamline workflows, reduce human variability and optimize performance, delivering consistent and repeatable outcomes without an expensive upgrade
- Activity-based workflows and intuitive, iconbased navigation screens
- Integration smart features to deploy advisory, process and directional drilling automation and industry-leading performance tools to accelerate ROP

SmartRig Fleet Specifications

Feature	PACE-X	PACE-B	PACE-M			PACE-S	PACE-F
7 Catare			M750	M800	M1000	TAGE G	17.02
Drawworks	2,000 HP Minimum 3,000 Available	2,000 HP	2,000 HP	3,000 HP	3,000 HP	2,000 HP	2,000 HP
Mast Rating	800,000 lbs Minimum 1,000,000 lbs Available	800,000 lbs	750,000 lbs	1,000,000 lbs	1,000,000 lbs	750,000 lbs	800,000 lbs
Setback Capacity	750,000 lbs 30,000 ft @ 5" DP	750,000 lbs 30,000 ft @ 5" DP	640,000 lbs 25,000 ft @ 5" DP	750,000 lbs 30,000 ft @ 5" DP	900,000 lbs 35,000 ft @ 5" DP	700,000 lbs 27,000 ft @ 5" DP	800,000 lbs 22,000 ft @ 5" DP
Substructure	Box-on-Box	Box-on-Box	Swing-Up, Hydraulic	Swing-Up, Hydraulic	Swing-Up, Hydraulic	Swing-Up, Hydraulic	Swing-Up, Hydraulic
Walking Capacity	Walking System 120 ft Minimum - More Available	Walking System 150 ft Minimum - More Available	Walking System 150 ft Minimum - More Available	Walking System 150 ft Minimum - More Available	Walking System 250 ft	Walking System 100 ft Minimum - More Available	Walking System 150 ft Minimum - More Available
Top Drive	500 Ton AC High Torque - 51,400 ft-Ibs Torque Rating						
Engines / Generators	4 x 3512 With 1,365 kw Generator						

With 1,365 kw Generato

3 x 1,600 HP AC 7,500 psi Mud Pressure

Remote Operated Wrench – 80,000 ft lbs minimum – TM100 and TM 120 Available Remote Operated Hydraulic Catwalk Rotating Mousehole

www.nabors.com/for-operators/onshore-smartrigs/

Mud Pumps

Pipe Handling